



LUFILITIONOFFICE OFFICE OFFICE

LV600 PLUS





www.greenclimber.com.au

- f greenclimberaustralia
- greenclimberau

REMOTE CONTROLLED SLOPE MOWER

SPECIFICATIONS LV600 PLUS	
Engine	Kohler Turbo 42 Kw
Horsepower	56HP
Torque	225 Nm
Fuel type	Diesel
Fuel capacity (L)	32
Ground speed (Km/hr)	8
Standard Flail Weight	250kg
Machine Weight only	1470kg
Flail Speed	3300 rpm
Machine Height	1180mm
Machine Length	2160mm
Machine Width	1360-1760mm
Main attachment pump	(piston closed loop) 83 lt/min @320bar
Service pump	24 lt/min @ 180bar
Extendable undercarriage	(Closed) 1360 mm (Open) 1760 mm
Attachment sideshifting	(Hydraulic) 400 mm + (Mechanical) 400 mm
	Dallat Forka Ctump Crinder
Attachments	Pallet Forks Stump Grinder
	Loader Bucket Grapple Gruffalo Sprayer
	op. a.y.
	Heavy Duty Forestry Flail

FEATURES		
Powerful 3-cylinder KOHLER TURBO INTERCOOLER COMMON RAIL ENGINE	Patented undercarriage to climb steep slopes and anti-de-tracking system of the tracks.	
Engine lubrication patented by MDB for continuous use on steep slopes of up to 60°.	The reversible fan and an oversized radiator allow for continuous work at full power also at high outside temperatures.	
The integrated hydraulic side- shifting plate allows for lateral adjustment of the attachment of up to 400mm.	The totally hydraulic floating attachment plate of the mulcher allows the tool to remain constantly in contact with the floor.	
Integrated cylinders allow for widening of the tracks from 1360mm up to 1760mm (patented system).	2 auxiliary lines (1 prop. + 1 on\off). Tow Hook.	